



Applications

Rubber hose for LPG (gas cylinders, heaters, welding, and LPG lines)

Advantages

- Uniform quality and durable performance levels.
- Manufactured to the recognised British standard for LPG hose.



Technical description


Inner tube: NBR/SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, orange, smooth.

Temperature range: -30 °C to +80 °C.

Branding: with a discontinuous succession of reversed trapeziums printed in blue ink, and between each sequence of trapeziums, printed alternately in blue ink :



TRELLEBORG

and

BS 3212 : 1991/2 / Ø / HIGH PRESSURE LPG

Standard / approval: BS 3212/2.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
4.8 ± 0.4	4.10	13.0 ± 0.7	20	60	45	0.17	20	60230	●
							40	60231	●
							50	60232	●
							60	60233	1
							80	60234	1
6.3 ± 0.5	3.85	14.0 ± 0.7	20	60	55	0.18	100	60235	1
							20	60101	●
							40	60102	●
							50	60100	●
							60	60103	1
8.0 ± 0.5	4.00	16.0 ± 0.8	20	60	65	0.22	80	60104	1
							100	60132	1
							20	60397	●
							40	60398	●
							50	60386	●
10.0 ± 0.5	4.00	18.0 ± 0.8	20	60	75	0.25	60	60399	●
							80	60400	●
							100	60401	●
							20	60261	●
							40	60262	●
							50	60263	●
							60	60264	●
							80	60265	●
							100	60266	●

● = Stock item.

1 = Non stock, min. quantity = 3000 m.