



Applications

Rubber tube for milking equipment.

Advantages

- Suitable for milking machines of the main O.E.M.'s.
- Easy to clean having a perfectly smooth inner tube.



Technical description

Inner tube: food quality NR/SBR, black, smooth.

Temperature range: -30 °C to +100 °C.

Branding:

- Longitudinal stripe printed in green ink, with the food-grade symbol, as well as the RAL's acronym,

- on the opposite side recessed marking:

ID x OD – month – year

Standard / approval:

Food grade approval from the French Institute of Poitiers (IANESCO) and BgVV in Germany.

ID mm		Wall thickness mm	OD mm		Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
6.3	-0/+1	3.35	13.0	±1	1	3	18	0.12	* 40	70656	1
7.0	-0/+1	3.00	13.0	±1	1	3	20	0.11	** 0.23	46303	●
7.0	-0/+1	3.00	13.0	±1	1	3	20	0.11	* 40	46304	●
8.0	-0/+1	4.00	16.0	±1	1	3	25	0.17	* 40	46309	●
10.0	-0/+1	5.00	20.0	±1	1	3	30	0.27	* 40	46311	●
12.0	-0/+1	5.00	22.0	±1	1	3	35	0.31	25	46313	●
13.0	-0/+1	5.00	23.0	±1	1	3	45	0.32	20	46317	●
13.0	-0/+1	6.00	25.0	±1	1	3	34	0.41	20	46318	●
14.0	-0/+1	5.50	25.0	±1	1	3	50	0.38	20	46319	●
15.0	-0/+1	6.00	27.0	±1	1	3	55	0.45	20	46320	●
16.0	-0/+1	6.00	28.0	±1	1	3	60	0.47	20	46321	●
19.0	-0/+1	6.50	32.0	±1	1	3	90	0.59	15	12101	2
Twin hose											
7.0 +7.0	-0/+1	3.00	13.0	±1	1	3	17	0.22	20	46306	●

● = Stock item.

1 = Non stock, min. quantity = 4500 m.

2 = Non stock, min. quantity = 2000 m.

* = Will be delivered either in 40 meters lengths or 2 x 20 m (packed in carton).

** = Packaged in box of 1000 units.