



## Applications

Discharge under pressure or gravity flow of corrosive products such as acids and alkalis.

## Advantages

- Tube can be cut to length as required.
- Flexible and easy to handle.
- Excellent resistance to low temperatures.



## Technical description

**Inner tube:** chemical resistant NR, beige, smooth.

**Cover:** fabric impression.

**Temperature range:** - 40 °C to +70 °C.

**Electrical properties:** non conductive.

**Branding:** unbranded.

ID mm		Wall thickness mm	OD mm		Max. pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
15.0	-0/+1	5.0	25.0 ± 1		1	-	-	0.34	20	200387	1
20.0	-0/+1	5.0	30.0 ± 1		1	-	-	0.43	20	200840	•
20.0	-0/+1	5.0	30.0 ± 1		1	-	-	0.43	40	200841	1
25.0	-0/+1	5.0	35.0 ± 1		1	-	-	0.51	20	200843	•
25.0	-0/+1	5.0	35.0 ± 1		1	-	-	0.51	40	200844	1
30.0	-0/+1	5.0	40.0 ± 1		1	-	-	0.59	20	200846	•
30.0	-0/+1	5.0	40.0 ± 1		1	-	-	0.59	40	200847	1
35.0	-0/+1	5.0	45.0 ± 1		1	-	-	0.67	20	200849	•
35.0	-0/+1	5.0	45.0 ± 1		1	-	-	0.67	40	200850	1
40.0	-0/+1	5.0	50.0 ± 1		1	-	-	0.76	20	200852	•
40.0	-0/+1	5.0	50.0 ± 1		1	-	-	0.76	40	200853	1
50.0	-0/+1	5.0	60.0 ± 1		1	-	-	0.92	20	200855	•
50.0	-0/+1	5.0	60.0 ± 1		1	-	-	0.92	40	200856	1
60.0	-0/+1	5.0	70.0 ± 1.5		1	-	-	1.09	20	200858	•
60.0	-0/+1	5.0	70.0 ± 1.5		1	-	-	1.09	40	200874	2
80.0	-0/+1	7.5	95.0 ± 1.5		1	-	-	2.12	20	200876	•
80.0	-0/+1	7.5	95.0 ± 1.5		1	-	-	2.12	40	200877	2

• = Stock item.

1 = Non stock, min. quantity = 400 m.

2 = Non stock, min. quantity = 200 m.