



Applications

Pressure service line for ester, ketone, alcohol based paints, and numerous chemicals.

Advantages

- Hose cover resistant to splashing of corrosive chemicals.
- Absence of silicone in tube walls.
- Hose remains flexible within a wide temperature range.
- Antistatic tube.



Technical description

Inner tube: chemical resistant EPDM, black, smooth.

Reinforcement: synthetic textile.

Cover: chemical and weather resistant EPDM, green, smooth.

Temperature range: -30 °C to +100 °C.

Electrical properties: conductive tube $R < 10^6 \Omega/m$.

Branding: with a discontinuous succession of reversed trapeziums printed in black ink, and between each sequence of trapeziums, printed alternately in black ink:



TRELLEBORG

and

SOLVYKLER

Couplings / Fittings

Special paint hose couplings are recommended.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
6.0 ± 0.4	3.5	12.6 ± 0.5	20	60	60	0.13	20	60304	●
							40	60305	●
							80	60306	1
							120	60307	1
8.0 ± 0.5	3.5	15.0 ± 0.6	20	60	70	0.16	20	60308	●
							40	60309	●
							80	60310	1
							120	60311	1
9.0 ± 0.5	3.5	16.0 ± 0.6	20	60	85	0.17	20	60281	●
							40	60282	●
							80	60283	1
							120	60285	1
10.0 ± 0.5	4.0	18.0 ± 0.6	20	60	90	0.22	20	60312	●
							40	60313	●
							80	60314	1
							120	60315	1
13.0 ± 0.6	4.0	21.0 ± 0.7	20	60	110	0.27	20	60718	●
							40	60719	●
							80	60720	2
							120	60721	●
16.0 ± 0.8	4.0	24.0 ± 1.0	20	60	130	0.32	20	70139	●
							40	70140	●
							80	70141	●
							20	70142	●
20.0 ± 0.8	4.5	29.0 ± 1.0	20	60	170	0.44	40	70143	●
							80	70144	●
							20	70145	●
25.0 ± 1.2	4.5	34.0 ± 1.5	20	60	150	0.54	40	70146	●
							80	70147	2

● = Stock item.

1 = Non stock, min. quantity = 3000 m.
2 = Non stock, min. quantity = consult us

H3 3 38 03 C / 25 09 2004