



Applications

For professional and industrial high pressure cleaning.
Suitable for mobile pressure washers and fixed installations.
Also for reel mounted applications.

Advantages

- Oil and detergent resistant, smooth cover.
- Wear and weather resistant.
- High temperature resistance.
- Highly flexible and kink resistant.
- Specially developed for professional and industrial high pressure cleaning.
- Dimensions according to DIN 20022 1 ST.



Technical description

Inner tube: NBR/SBR, black, smooth.

Reinforcement: steel, one braid.

Cover: SBR/NBR, black, smooth.

Temperature range: -40 °C to +180 °C.

Branding: continuous recessed branding.

TRELLJET 521 – ND – inches – WP 210 bar/3045 PSI – Max 180 °C – quart./year

ND	ID mm	Wall thickness mm	OD mm	Reinforcement diameter mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
08	7.9 + 0.6 / - 0.2	3.40	14.7 ± 0.7	12.7 ± 0.3	210	840	70	0.24	< 100	2909250	•
									≥ 100	2910070	•
10	9.5 + 0.6 / - 0.2	3.75	17.0 ± 0.7	14.8 ± 0.3	210	840	75	0.32	< 100	2862740	•
									≥ 100	2910080	•
13	12.7 + 0.8 / - 0.4	3.90	20.5 ± 0.8	18.2 ± 0.3	210	840	80	0.39	< 100	2910090	•
									≥ 100	2910100	•

• = Stock item.