



Applications

Metered fuel delivery equipment for petrolpump: regular and super grade petrol, unleaded petrol, and diesel oil.

Advantages

- Good resistance to ageing and abrasion from repeated dragging over oily floors.
- Complies with European standard.
- Can be supplied ready fitted with couplings.



Technical description

Inner tube: petrol resistant NBR, black, smooth.


Reinforcement: synthetic textile, braids.

Cover: oil and weather resistant NBR/PVC, black, smooth.

Temperature range: - 25 °C to + 65 °C.

Electrical properties: conductive tube $R < 10^6 \Omega / \text{lg}$.

Branding: continuous embossed marking :

 TRELLEBORG VOLUKLER - EN 1360/1 - ND - 16 bar - Ω - Quater / Year

Standard / approval: EN 1360 type 1.

Complementary information

Blue, red, yellow or green cover are available upon request.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item		
15.0	± 0.8	5.0	25.0	± 0.9	16	48	75	0.40	20	61771	2
									40	61772	2
									80	61773	2
									100	61774	2
									120	61775	•
16.0	± 0.8	4.5	25.0	± 0.9	16	48	80	0.37	20	61776	•
									40	61777	•
									80	61778	•
									120	61779	•
									18.0	± 0.8	6.0
40	61781	1									
80	61782	1									
100	61783	1									
120	61784	•									
19.0	± 0.8	6.0	31.0	± 0.9	16	48	100	0.60	20	61785	•
									40	61786	•
									80	61787	•
									120	61788	•
									25.0	± 1.0	6.0
40	61790	•									
80	61791	•									

• = Stock item.

1 = Non stock, min. quantity = 2000 m.

2 = Non stock, min. quantity = 3000 m.