



Applications

For pneumatic tooling or pneumatic control lines (e.g. paint spray guns)

Advantages

- Static conductive tube.
- Very flexible hose especially at low temperatures.
- Suitable for hot water.



Technical description

Inner tube: EPDM, black, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, blue, smooth.

Temperature range: -40 °C to +100 °C.

Electrical properties: conductive tube $R < 10^6 \Omega/m$.

Branding: with a discontinuous succession of reversed trapeziums printed in black ink, and between each sequence of trapeziums, printed alternately in black ink :



TRELLEBORG

and

VULCAIN + $R < 10^6 \Omega/m$.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
6.0 ± 0.4	3.0	12.0 ± 0.5	20	60	25	0.11	20	129662	●
							40	129663	●
							120	129665	●
7.0 ± 0.5	3.5	14.0 ± 0.6	20	60	25	0.15	20	129667	●
							40	129668	1
							120	129669	1
8.0 ± 0.5	3.5	15.0 ± 0.6	20	60	30	0.16	20	129670	●
							40	129671	●
							120	129672	●
9.0 ± 0.5	3.5	16.0 ± 0.6	20	60	35	0.18	20	129673	●
							40	129675	●
							120	129676	1
10.0 ± 0.5	4.0	18.0 ± 0.6	20	60	40	0.23	20	129678	●
							40	129679	●
							120	129680	●
12.0 ± 0.6	4.0	20.0 ± 0.7	20	60	60	0.26	20	129681	1
							40	129682	1
							120	129684	1

● = Stock item.

1 = Non stock, mini. quantity = 2000 m.