



Applications

Water discharge.

Advantages

- Coils flat for easy storage and handling.
- Light weight.
- Long length.
- Wide range of diameters.



Technical description

Inner tube: PVC, black, smooth.
Reinforcement: synthetic textile.
Cover: PVC, blue, smooth.
Temperature range: -10 °C to +40 °C.
Branding: unbranded.

Complementary information

Working pressure and bursting pressure mentioned are valid at +20 °C.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
19.0			13	39	-	0.17	50	125216	1
25.0			12	36	-	0.23	50	124652	1
32.0			10	30	-	0.25	50	83815	1
							100	126332	1
35.0			8	24	-	0.29	50	200935	•
							100	200934	•
38.0			8	24	-	0.30	50	83829	1
							100	83831	1
41.0			8	24	-	0.32	50	200939	•
							100	200938	•
45.0			8	24	-	0.35	50	201333	•
							100	201334	1
50.0			8	24	-	0.41	50	200943	•
							100	200942	•
63.0			8	24	-	0.58	50	201335	•
							100	201336	•
70.0			8	24	-	0.62	50	201337	•
							100	201338	1
75.0			8	24	-	0.70	50	200949	•
							100	200948	1
84.0			8	24	-	0.80	50	125549	1
							100	122949	1
90.0			8	24	-	0.86	50	201339	•
							100	201340	1
100.0			8	24	-	1.05	50	200955	•
							100	200954	1
110.0			8	24	-	1.15	50	126124	1
							100	126302	1
150.0			4	12	-	1.60	50	200959	•
							100	200958	1
200.0			3	9	-	2.40	50	200952	1
							100	200953	1

• = Stock item.
 1 = Non stock, min. quantity = 200 m.