



Applications

Water discharge for all types of industrial and agricultural medium pressure applications in harsh environments.

Advantages

- Extremely resistant to ageing and atmospheric conditions.
- Coils flat for easy storage and handling.
- A robust construction to resist impact, kinking, and abrasion.
- For fluids up to 100 °C.
- Wide range of diameters.



Technical description


Inner tube: EPDM, white, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, brik-red, fabric impression.

Temperature range: -30 °C to +100 °C.

Branding: by transfer stripe showing a discontinuous of black trapeziums with:

 TRELLEBORG printed in brik-red on each trapezium

COLORADO - S printed in black between trapeziums.

Standard / approval: NF - EN ISO 1403.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
30,0	4,25 ± 0,75	39,0 ± 1,00	10	28	240	0,71	20	62278	●
							40	62277	●
32,0	4,25 ± 0,75	41,0 ± 1,00	10	28	260	0,75	20	50549	1
							40	50550	1
35,0	4,25 ± 0,75	44,0 ± 1,00	10	28	280	0,81	20	62288	●
							40	62287	●
40,0	4,25 ± 0,75	49,0 ± 1,00	10	28	320	0,91	20	62298	●
							40	62297	●
45,0	4,25 ± 0,75	54,0 ± 1,00	10	28	360	1,01	20	62303	●
							40	62302	●
50,0	4,25 ± 0,75	60,0 ± 1,00	10	28	500	1,26	20	62308	●
							40	62307	●
60,0	4,25 ± 0,75	70,0 ± 1,50	10	28	600	1,51	20	62318	●
							40	62317	●
65,0	4,25 ± 0,75	76,5 ± 1,50	10	28	650	1,80	20	200059	2
							40	200060	2
70,0	5,75 ± 1,00	81,5 ± 1,50	10	28	700	2,01	20	62328	●
							40	62327	●
75,0	5,75 ± 1,00	86,5 ± 1,50	10	28	750	2,15	20	200061	2
							40	200062	2
80,0	5,75 ± 1,00	92,0 ± 1,50	10	28	800	2,43	20	62336	●
							40	62337	●
89,0	5,75 ± 1,00	101,0 ± 1,50	10	28	900	2,71	20	62339	●
							40	62349	●
100,0	5,75 ± 1,00	112,0 ± 1,50	10	28	1000	3,00	20	62341	●
110,0	5,75 ± 1,00	121,5 ± 2,00	5	12,5	1100	3,239	10	200005	3
120,0	5,75 ± 1,00	131,5 ± 2,00	5	12,5	1200	3,41	10	200006	3

● = Stock item.

1 = Non stock, min. quantity = 400 m..

2 = Non stock, min. quantity = 200 m..

3 = Non stock, min. quantity = 120 m..