



Applications

Heavy duty handling of oil charged compressed air (tanker duty).
High pressure compressors and other equipment used on public works sites.

Advantages

- Very robust due to the steel reinforcement.
- Resistant to atmospheric conditions and contact with greasy floors.
- Resistant to mineral oils.



Technical description



Inner tube: NSBR, black, smooth.

Reinforcement: steel braids or steel cords.

Cover: SBR, yellow, fabric impression.

Temperature range: -30 °C to +95 °C.

Branding: by transfer stripe showing a discontinuous of red trapeziums with :

 TRELLEBORG printed in yellow on each trapezium
 and  METALAIR printed in red between trapeziums

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item	
19.0	-0 / +1.0	6.75	32.5 ± 1.5	40	160	115	0.84	20	75408	1
								40	70641	1
25.0	-0 / +1.0	7.00	39.0 ± 1.5	40	160	150	1.12	20	127603	1
								40	70642	1
32.0	-0 / +1.0	7.00	46.0 ± 1.5	40	160	230	1.45	20	70643	2
								40	70644	2
38.0	-0 / +1.0	7.50	53.0 ± 1.5	40	160	280	1.75	20	70645	2
								40	70646	2
50.0	-0 / +1.5	8.00	66.0 ± 1.5	40	160	300	2.43	20	75418	3
								40	70647	•
60.0	-0 / +1.5	8.00	76.0 ± 1.5	40	160	380	2.98	20	75425	4

• = Stock item.

1 = Non stock, mini. quantity = 1000 m.

2 = Non stock, mini. quantity = 500 m.

3 = Non stock, mini. quantity = 2 x 20 m.

4 = Non stock, mini. quantity = 200 m.