



Applications

Pressure service line for benzene, toluene, and xylene based paints, lacquer, varnish, and certain chemicals.
Also for industrial paint spray equipment.

Advantages

- Hose cover resistant both to abrasion and to corrosive chemicals.
- Absence of silicone.
- Conductive tube.



Technical description

Inner tube: solvent paints resistant NBR, black, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant NBR/PVC, green, smooth.

Temperature range: -20 °C to +100 °C.

Electrical properties: conductive tube $R < 10^6 \Omega/m$.

Branding: with a discontinuous succession of reversed trapeziums printed in black ink, and between each sequence of trapeziums, printed alternately in black ink:



TRELLEBORG

and

MULTIKLER

Couplings / Fittings

Special paint hose couplings are recommended.

| ID mm | Wall thickness mm | OD mm | Working pressure bar | Bursting pressure bar | Bending radius mm | Weight kg/m | Length m | Article No. | Stock item |
|------------|-------------------------|------------|----------------------------|-----------------------------|-------------------------|----------------|-------------|----------------|---------------|
| 6.0 ± 0.4 | 3.50 | 12.6 ± 0.5 | 20 | 60 | 60 | 0.14 | 20 | 64196 | ● |
| | | | | | | | 40 | 64197 | ● |
| | | | | | | | 80 | 64198 | 1 |
| | | | | | | | 120 | 64199 | 1 |
| 8.0 ± 0.5 | 3.50 | 15.0 ± 0.6 | 20 | 60 | 70 | 0.17 | 20 | 64201 | ● |
| | | | | | | | 40 | 64202 | ● |
| | | | | | | | 80 | 64203 | 1 |
| | | | | | | | 120 | 64204 | ● |
| 9.0 ± 0.5 | 3.50 | 16.0 ± 0.6 | 20 | 60 | 85 | 0.19 | 20 | 64219 | 1 |
| | | | | | | | 40 | 64220 | ● |
| | | | | | | | 80 | 64221 | 1 |
| | | | | | | | 120 | 64222 | 1 |
| 10.0 ± 0.5 | 3.75 | 17.5 ± 0.6 | 20 | 60 | 90 | 0.24 | 20 | 64207 | ● |
| | | | | | | | 40 | 64208 | ● |
| | | | | | | | 80 | 64209 | 1 |
| | | | | | | | 120 | 64210 | 1 |
| 13.0 ± 0.6 | 4.00 | 21.0 ± 0.7 | 20 | 60 | 110 | 0.28 | 20 | 64211 | ● |
| | | | | | | | 40 | 64212 | ● |
| | | | | | | | 80 | 64213 | 1 |
| | | | | | | | 120 | 64214 | 1 |
| 16.0 ± 0.7 | 4.50 | 25.0 ± 0.8 | 20 | 60 | 130 | 0.38 | 20 | 64215 | ● |
| | | | | | | | 40 | 64216 | ● |
| | | | | | | | 80 | 64217 | 1 |
| | | | | | | | 120 | 64218 | 1 |

● = Stock item.

1 = Non stock, min. quantity = 3000 m.