

TRELLJET 560



Applications

For heavy duty professional and industrial high pressure cleaning.
Suitable for mobile pressure washers and fixed installations.
Also for reel mounted applications.

Advantages

- Long service life.
- Oil and detergent resistant, smooth cover.
- Wear and weather resistant.
- High temperature resistance.
- Highly flexible and kink resistant.



Technical description

Inner tube: NBR/SBR, black, smooth.
Reinforcement: steel, two braid.
Cover: SBR/NBR, black, smooth.
Temperature range: -40 °C to +180 °C.
Branding: continuous recessed branding

TRELL-JET 560 - ND - inches - WP 650 bar/9560 PSI - Max 180 °C - quart./year

ND	ID mm	Wall thickness mm	OD mm	Reinforcement diameter mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
08	7.9 +0.6 / -0.2	3.55	15.0 ±0.7	12.7 ±0.3	650	1600	65	0.31	< 100	2909260	●
									≥ 100	2910220	●
10	9.5 +0.6 / -0.2	3.80	17.1 ±0.7	14.9 ±0.3	650	1600	70	0.38	< 100	2862190	●
									≥ 100	2912060	●

● = Stock item.

H3 3 22 23 1 /04 02 2001