

TRELLJET 561



Applications

For professional and industrial high pressure cleaning.
Suitable for mobile pressure washers and fixed installations.
Also suits reel mounted applications.

Advantages

- Oil and detergent resistant, smooth cover.
- Wear and weather resistant.
- High temperature resistance.
- Light weight, flexible and kink resistant.



Technical description

Inner tube: NBR/SBR, black, smooth.

Reinforcement: steel, one braid.

Cover: SBR/NBR, black, smooth.

Temperature range: -40 °C to +180 °C.

Branding: continuous recessed branding

TRELL-JET 561 - ND - inches - WP 400 bar/5880 PSI - Max 180 °C - quart./year

ND	ID mm	Wall thickness mm	OD mm	Reinforcement diameter mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
06	6.4 +0.6 / -0.2	2.65	11.7 ±0.7	9.8 ±0.3	400	1000	50	0.16	< 100	2909810	●
									≥ 100	2913930	●
08	7.9 +0.6 / -0.2	2.75	13.4 ±0.7	11.5 ±0.3	400	1000	60	0.19	< 100	2909240	●
									≥ 100	2910040	●
10	9.5 +0.6 / -0.2	3.00	15.5 ±0.7	13.6 ±0.3	400	1000	70	0.25	< 100	2862110	●
									≥ 100	2910000	●

● = Stock item.

H3 3 22 13 1 /04 02 2001