

TRELLJET 580



Applications

For heavy duty, professional and industrial (non-marking) high pressure cleaning for example, the food industry and in public baths.

Suitable for mobile pressure washers and fixed installations.

Also for other reel mounted applications.

Advantages

- Non-staining, oil and detergent resistant, smooth cover.
- Long service life.
- Wear and weather resistant.
- High temperature resistance.
- Highly flexible and kink resistant.
- Specially developed for professional and industrial heavy duty, high pressure cleaning.



Technical description

Inner tube: NBR/SBR, black, smooth.

Reinforcement: steel, two braid.

Cover: SBR/NBR, blue, smooth.

Temperature range: -40 °C to +180 °C.

Branding: continuous recessed branding

TRELL-JET 580 - ND - inches - WP 650 bar/9560 PSI - Max 180 °C - quart./year

or

TRELL-JET 580 - ND 13 - 1/2" - WP 500 bar/7350 PSI - Max 180 °C - quart./year

ND	ID mm	Wall thickness mm	OD mm	Reinforcement diameter mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
08	7.9 +0.6 / -0.2	3.55	15.0 ±0.7	12.7 ±0.3	650	1600	65	0.31	< 100	2862200	●
									≥ 100	2910310	●
10	9.5 +0.6 / -0.2	3.80	17.1 ±0.7	14.9 ±0.3	650	1600	70	0.38	< 100	2862210	●
									≥ 100	2910370	●
13	12.7 +0.8 / -0.4	3.75	20.2 ±0.8	18.1 ±0.3	500	1200	75	0.47	< 100	2909280	●
									≥ 100	2910420	●

● = Stock item.

H3 3 22 25 1 /04 02 2001