

# TRELLJET 581



## Applications

For professional and industrial (non-marking) high pressure cleaning, for example in the food industry and in public baths. Suitable for mobile pressure washers and fixed installations.

Also for reel mounted applications.

## Advantages

- Non-staining, oil and detergent resistant, smooth cover.
- Wear and weather resistant.
- High temperature resistance.
- Highly flexible and kink resistant.



## Technical description

**Inner tube:** NBR/SBR, black, smooth.

**Reinforcement:** steel, one braid.

**Cover:** SBR/NBR, blue, smooth.

**Temperature range:** -40 °C to +180 °C.

**Branding:** continuous recessed branding:

TRELL-JET 581 - ND - inches - WP 400 bar/5880 PSI - Max 180 °C - quart./year

or

TRELL-JET 581 - ND 13 - 1/2" - WP 350 bar/5000 PSI - Max 180 °C - quart./year

ND	ID mm	Wall thickness mm	OD mm	Reinforcement diameter mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
06	6.4 +0.6 / -0.2	2.65	11.7 ±0.7	9.8 ±0.3	400	1000	50	0.16	< 100	2909290	●
									≥ 100	2910430	●
08	7.9 +0.6 / -0.2	2.75	13.4 ±0.7	11.5 ±0.3	400	1000	60	0.19	< 100	2909300	●
									≥ 100	2910440	●
10	9.5 +0.6 / -0.2	3.00	15.5 ±0.7	13.6 ±0.3	400	1000	70	0.25	< 100	2862220	●
									≥ 100	2910450	●
13	12.7 +0.8 / -0.4	3.00	18.7 ±0.8	16.7 ±0.3	350	900	80	0.31	< 100	2909310	●
									≥ 100	2910470	●

● = Stock item.

H3 3 22 27 1 /04 02 2001