

TRELLJET 681



Applications

For professional and industrial high pressure cleaning in the food industry and in public baths.

Suitable for mobile pressure washers and fixed installations.

Also for reel mounted applications.

Advantages

- Crush resistant.
- Non-staining, wear and weather resistant, smooth cover.
- High temperature resistance
- Highly flexible and kink resistant.



Technical description

Inner tube: NBR/SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: SBR/NBR, blue, smooth.

Temperature range: -40 °C to +120 °C.

Branding: continuous recessed branding

TRELL-JET 681 - ND - inches - WP 200 bar/2900 PSI - Max 120 °C - quart./year

ND	ID mm	Wall thickness mm	OD mm	Reinforcement diameter mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
10	9.5 + 0.6 / - 0.2	4.5	18.5 ± 0.8	15.0 ± 0.3	200	500	60	0.29	< 100	2910630	●
									≥ 100	2910640	●
13	12.7 + 0.8 / - 0.4	4.5	21.7 ± 0.8	18.3 ± 0.3	200	500	70	0.32	< 100	2910590	●
									≥ 100	2910600	●

● = Stock item.

H3 3 22 29 1 /04 02 2001