

VULPANE EN 559



Applications

Rubber hose for LPG (gas cylinders, heaters, welding, and LPG lines).

Advantages

- Flexible and light weight for easy handling.
- Long, safe service life:
 - A hose cover particularly resistant to atmospheric conditions (ozone and hot spots).
 - Special, high quality rubber compounds.
 - Very strong textile reinforcement giving high safety factor.
- Clear branding showing gas symbol and date of manufacture.



Technical description

Inner tube: NBR/SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, orange, smooth.

Temperature range: -30 °C to +80 °C.

Branding: with a discontinuous succession of reversed trapeziums printed in black ink, and between each sequence of trapeziums, printed in black ink:

NF EN559-ISO 3821-GPL/MPS-Ø-2MPa(20bar)-[-30°C]

- CF - Year - Made in France

Standard / approval: EN 559 and ISO 382.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item	
5.0	± 0.4	3.00	11.0 ± 0.5	20	60	50	0.11	20	70483	1
								40	70484	1
6.3	± 0.5	2.85	12.0 ± 0.6	20	60	55	0.12	20	200010	•
								40	200009	•
								120	200008	•
8.0	± 0.5	3.00	14.0 ± 0.6	20	60	65	0.15	20	200013	•
								40	200012	•
								120	200011	•
9.0	± 0.5	3.00	15.0 ± 0.6	20	60	70	0.18	20	200551	•
								40	200552	•
								120	200553	•
10.0	± 0.5	3.50	17.0 ± 0.6	20	60	75	0.21	20	200016	•
								40	200015	•
								120	200014	•

• = Stock item

1 = Non stock, min. quantity = 5000 m.

H3 3 32 05 1 / 02 02 2001